

# Fireplace Chimney Power Cap Specification Sheet for ordering

Name: \_\_\_\_\_ Ph # ( ) \_\_\_\_ - \_\_\_\_\_

Address: \_\_\_\_\_ Fax# ( ) \_\_\_\_ - \_\_\_\_\_  
\_\_\_\_\_

Chimney Configuration: Round \_\_\_\_\_, Square \_\_\_\_\_, Rectangular \_\_\_\_\_

Liner Material: Porcelain \_\_\_\_\_, Stainless Steel \_\_\_\_\_, Other \_\_\_\_\_

(1) Chimney Liner Dimensions: L = \_\_\_\_\_, W = \_\_\_\_\_, or Dia. = \_\_\_\_\_

(2) Distance the Liner extends above the top of the bricks = \_\_\_\_\_

**Note:** If liner extends less than 4 ½ inches above bricks, place a spacer of same material and size to provide at least 4 ½ inches above bricks.

(3) Length of electrical control wire required = \_\_\_\_\_ (30' normally supplied)

**Note:** Low voltage electric cable is to run from the console control at the fireplace, through the outside wall and up to the Chimney Power Cap.

Special Instruction or Concerns: -----  
-----  
-----

Standard Power Cap finish is black.

Shipping Weight = 32 lbs (14.5kg)

Date: \_\_\_\_\_ Authorization: \_\_\_\_\_

**HMI HOYME MANUFACTURING INC.**

4512 – 39 Street, Camrose, Alberta , Canada T4V 2N5 Ph. (780) 672-6555 Fax (780) 672-6554  
Website: [www.hoyme.com](http://www.hoyme.com) E-mail: [hoyme@hoyme.com](mailto:hoyme@hoyme.com) Ph. (800) 661-7382 Fax (800) 661-8065